
Description:

TECHNOMELT 3113 is a hot melt adhesive designed for general purpose assembly operations and deep freeze applications. Excellent adhesion for bonding PP, PE materials etc.

This product is supplied in stick form for use with hot melt glue guns (e.g. Loctite Hot Melt Dispenser EQ AU)

Meets composition requirements of Indirect Food Additive Regulation 21 CFR 175.105 "Adhesives".

Typical Properties:

Appearance:	White stick of 12mm diameter and 38cm length
Viscosity:	12,000 - 24,000cps
Open Time:	Long (up to 50 sec at 180°C)
Set Time:	Medium

Directions for Use:

Glue sticks should be introduced to the feed of the glue gun but pressure should not be applied until the gun reaches operating temperature.

Note: Excessive pressure applied before the melt chamber has reached operating temperature may cause the adhesive to blow back either up to the inlet tube or internally around the seal.

Guns should not be left on indefinitely without purging the adhesive through, as this will cause the product to degrade and char.

Supplementary Products:

Loctite Hot Melt Dispenser EQ AU- Hand operated hot melt glue gun.

Limitations:

Requires suitable hand held glue gun.

Clean Up:

Mechanical

Storage and Handling:

Please read the Material Safety Data Sheet for this product BEFORE use. Store in a cool and dry place.

Please ensure that products classed as a dangerous good are stored in compliance with the applicable regulations.

Shelf Life:

Best used within 24 months from date of manufacture when stored under the above conditions in the original unopened containers.

DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.

All Technical Data Sheets are uncontrolled documents, copies are not automatically updated